


VDH-NK800B

16CH Network Video Recorder



- › Apply high end level NVR dedicate doC CPU, excellent image processing efficiency.
- › Support 4 SATA hard disks, Max. 10TB each.
- › Apply new generation H.265 compression technology, effective save lots of hard disk storage space.
- › Apply Embedded Linux system, effective avoid viruses and hackers.
- › Support 16CH IP Camera(1080P) Surveillance video.
- › Support IP Camera(5MP).
- › Support HD high resolution output.
- › USB flash drive removable storage device.
- › Support 3 user login in and use real-time monitoring function by client software or browser at same time.
- › Support Fuho plug-n-play IP Cam.
- › With P2P function, scan QR-Code on the smartphone app to get instant monitoring and playback, and increasing information security.
- › Support for automatic firmware updates.

SPECIFICATIONS

System- SoC : Linux SoC operation system:Linux

Storage- Built-in SATA interface x4, compatible with SATA/SATAII/SATAIII Hard disk(Max. 16TB)

Video And Other I/O Interface- Dual video output : HD/VGA output
USB 2.0 x2 – connect with mouse and USB device
Auto-MDIX. Ethernet x1- 10/100/ 1000 (IEEE 802.3 Type 10Base-T 、 IEEE 802.3u Type 100Base-TX) ;
Auto-MDIX

Network Protocol- Ipv4 / ARP / TCP / UDP / ICMP / SMTP / HTTP / RTP / RTSP / RTCP

Video Format- Support H.265 compression format

- Live / Playback-**
1. VGA at 30 FPS mode, capable monitoring Max.16 channel real-time video.
 2. Up to 4 channels of real-time video monitoring in 1080P@30 fps mode.
 3. Max.4 channel video playback by 1080P@ 30fps, Max.16 channel VGA@ 30fps.
 4. The real-time monitor screen support channel switch display—the single channel switch, group channel switch
 5. Record files playback can search by time and event. (IPCam displacement)
 6. Playback speed : Slow motion / fast motion multi-playback speed, single image format(forward or reverse)
 7. Capable doing multi-works as real-time monitoring, recording and playback at same time.

Event Notification- Event report content: Camera displacement detection, camera disconnection, hard disk damage.

Version updating is not going to inform, please check the on-going updating information

SPECIFICATIONS

Recording Mode-	Constant recording Schedule recording Motion Detection recording
Backup Management-	Backup output format: MP4 USB flash drive removable storage device
System Management-	1. Provide remote Client software, capable doing PC setting, real-time monitor and playback. 2. Hierarchical user right management, can setting user access rights or administrator, max.10 groups account. 3. Support 3 user login in and use real-time monitoring function by client software or browser at same time. 4. System usage records, record user login time, IP, monitoring images. 5. MS IE11 Browser: Support MS IE11
Device Support-	Support megapixel IP Camera monitor images
Power-	DC12V / 6A
Operating Temperature-	0-45 °C
Weight-	About 4.8KG
Size-	430mm x 370mm x 96mm (W x D x H)

Version updating is not going to inform, please check the on-going updating information