

# VIN-BS702-EA 2MP

## IP Camera



H.265



CMOS  
1/2.8"



C/CS  
mount



0~45°C



0.01 LUX



DC 12V



P.O.E

VIN-BS702E-EA  
(Optional)



- › Sony 2MP 1/2.8" COMS Image Sensor
- › Real-time H.265/H.264 Compression(dual codec)
- › Highest Resolution 1920x1080 @30 fps
- › Simultaneous Multiple Streams.
- › Support ONVIF international standard, best compatibility and integration

## SPECIFICATIONS

---

|                |                                                   |
|----------------|---------------------------------------------------|
| <b>System-</b> | Flash : 256MB<br>RAM : 512MB                      |
| <b>Sensor-</b> | SONY FullHD High Quality 1/2.8" CMOS Image Sensor |
| <b>Lens-</b>   | Support C/CS Mount lens                           |
| <b>IR Cut-</b> | Removable IR Cut filter                           |
| <b>Lux-</b>    | 0.01 Lux                                          |

---

|                     |                                                                                                                                                                                                |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Compression-</b> | H.265/H.264: 1920x1080 at 60 fps<br>H.265/H.264: 1280x720 at 60 fps<br>H.265/H.264: 640x480 at 60 fps<br>H.265 、 H.264 Multi-mode compression (Dual Codec)<br>Multi-mode compression streaming |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                          |                                                                                                                                                                    |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Video Adjustment-</b> | Resolution 、 Quality and bit rate<br>Time 、 Date or custom text and it's position<br>Brightness, Contrast, Saturation and Sharpness<br>AGC 、 AWB 、 AES 、 BLC 、 WDR |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                           |                                                                       |
|---------------------------|-----------------------------------------------------------------------|
| <b>Network Interface-</b> | 10 /100 Mbps RJ-45                                                    |
| <b>Protocol-</b>          | IPv4, TCP/IP, DHCP, HTTP, RTSP,SNTP,DNS                               |
| <b>Browser-</b>           | Microsoft Internet Explorer 6.0 or above<br>Safari, Chrome or Firefox |

|                                        |                                                               |
|----------------------------------------|---------------------------------------------------------------|
| <b>Alarm &amp; Event notification-</b> | Motion Detection<br>E-mail notification or upload file to FTP |
|----------------------------------------|---------------------------------------------------------------|

|              |                                                                 |
|--------------|-----------------------------------------------------------------|
| <b>User-</b> | Max. 8 users for live view simultaneously<br>User Authorization |
|--------------|-----------------------------------------------------------------|

|             |                          |
|-------------|--------------------------|
| <b>OTA-</b> | OTA for Firmware upgrade |
|-------------|--------------------------|

---

Version updating is not going to inform, please check the on-going updating information

## | SPECIFICATIONS

---

|                                |                                                                                                                             |
|--------------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| <b>I/O Port-</b>               | RJ-45 Ethernet port / Power input port DC 12V<br>Auto Iris / Audio input / output<br>Alarm output (2in 1out) / Reset button |
| <b>Power-</b>                  | DC12V or PoE IEEE802.3af Class 0 (optional)                                                                                 |
| <b>Power Consumption-</b>      | 3.6W                                                                                                                        |
| <b>Weight-</b>                 | N.W. : 345g                                                                                                                 |
| <b>Dimension-</b>              | 152 × 70 × 50 mm                                                                                                            |
| <b>Operating Environments-</b> | 0 ~ 45 °C                                                                                                                   |

---

Version updating is not going to inform, please check the on-going updating information