VIN-US730T-EA 1080P IP66

Electronic Auto AF motor lens IP cam

H.265 | CMOS 1/2.8" | Motorized zoom 2.8~12mm | 12 LEDS | 0 LUX

IR 100 m | DC 12V | 0~45°C







- Sony 2MP 1/2.8" COMS Image Sensor
- Built in electronic auto AF Lens motor, user friendly for remote config
- Real-time H.265/H.264 Compression(dual codec)
- Highest Resolution 1920x1080 @60 fps
- 12 High Power IR LEDs,IR Distance 100M
- Ultra-low illumination strengthens night monitoring
- Support ONVIF international standard, best compatibility and integration

VIN-US730T-EA Detailed Information

SPECIFICATIONS

system-	Flash：256MB
	RAM：512MB
Image Sensor-	SONY FullHD High Quality 1/2.8" CMOS Image Sensor
Lens-	Motorized / Automatic Zoom 2.8-12mm
IR-cut-	Removable IR-cut filter for day & night function
Low Lux-	0.001Lux
IR LED-	High Power IR LEDs x12

Video-	H.265/H2.64: 1920x1080 at 60 fps
	H.265/H.264: 1280x720 at 60 fps
	H.265/H.264: 640x480 at 60 fps
	H.265、H.264 Multi-mode compression (Dual Codec)
	Support Simultaneous multiple streams
Image Settings-	Adjustable image size,quality, and bit rate
	Time/Date stamp and text caption overlay
	Configurable brightness, contrast, saturation, sharpness, white balance and exposure
	Have: AGC、AWB、AES、BLC、WDR Features
Electronic Shutter-	1/2 ~ 1/100,000 Sec
Networking Interface-	10 /100 Mbps,RJ-45
Protocol-	IPv4,TCP/IP, DHCP, HTTP, RTSP,SNTP,DNS
browser-	Microsoft Edge、Safari、Chrome or Firefox
Alarm and Event Management-	Motion Detection
	Event notification using SMTP or FTP
Users-	clients on-line monitoring at the same time
	Multi-level user access control with password protection

Version updating is not going to inform, please check the on-going updating information

SPECIFICATIONS

Maintenance-	Supports online firmware upgrade
I/O-	RJ-45 Ethernet x 1,DC12V
Power-	DC12V
Max. Power Consumption-	3.6W(IR OFF)、18W(IR ON)
Weight-	N.W.：1170g
Dimension-	255mm x 75.3mm x 75mm
Operating Environments-	0 ~ 45 °C
IP Rating-	IP66

Version updating is not going to inform, please check the on-going updating information