

VIN-US730VT-E4 1080P IP66

Electronic Auto AF motor lens IP cam



- > Sony 2MP 1/2.8" COMS Image Sensor
- > Built in electronic auto AF Lens motor, user friendly for remote config
- > Real-time H.265/H.264 Compression(dual codec)
- > Highest Resolution 1920*1080 @60 fps
- > HI-P 12 LED, IR Distance 100M
- > Ultra-low illumination strengthens night monitoring
- > Support ONVIF international standard, best compatibility and integration

SPECIFICATIONS

system- Flash : 256MB

RAM : 512MB

Image Sensor- SONY FullHD High Quality 1/2.8" CMOS Image Sensor

Lens- Auto Varifocal 5-50mm

IR-cut- Removable IR-cut filter for day & night function

Low Lux- 0.001Lux

Compression- HI-P 12 IR LED

Video- H.265/H2.64: 1920x1080 at 60 fps

H.265/H.264: 1280x720 at 60 fps

H.265/H.264: 640x480 at 60 fps

H.265 、 H.264 Multi-mode compression (Dual Codec)

Support Simultaneous multiple streams

Image Settings- Adjustable image size,quality, and bit rate

Time/Date stamp and text caption overlay

Configurable brightness, contrast, saturation, sharpness, white balance and exposure

Have: AGC 、 AWB 、 AES 、 BLC 、 WDR Features

Electronic Shutter- 1/2 ~ 1/100,000 Sec

Networking Interface- 10 /100 Mbps,RJ-45

Protocol- IPv4,TCP/IP, DHCP, HTTP, RTSP,SNTP,DNS

browser- Microsoft Internet Explorer 6.0 or above

Safari, Chrome or Firefox

Alarm and Event Management- Motion Detection

Event notification using SMTP or FTP

Users- clients on-line monitoring at the same time.

Multi-level user access control with password protection.

Version updating is not going to inform, please check the on-going updating information

SPECIFICATIONS

Maintenance-	Supports online firmware upgrade
I/O-	RJ-45 Ethernet x 1,DC12V
Power-	DC12V
Max. Power Consumption-	3.6W(IR OFF) 、 10W(IR ON)
Weight-	N.W. : 650g
Dimension-	255mm x 75.3mm x 75mm
Operating Environments-	0 ~ 45 °C
IP Rating-	IP66

Version updating is not going to inform, please check the on-going updating information