



32 CH 4M H.265

Network Video Recorder



2017 JUL. V1.0























IP Surveillance

VDH-NXE872

- ·Pentaplex Operation: which can Record / Playback / Remote Connection / mobile phone watch / video backup.
- ·Support 8 fixed internal Hard Drives, single hard drive can be up to 8TB.
- Support HD output (4K2K)
- ·Support real-time recording and playback
- ·Support IE /Firefox/Safari. On-line recording/playback and user management
- ·Support HTTP, DHCP, DDNS, NTP, SMTP, FTP, DNS, UPNP, PPPoE, IP rights, IP search and other Internet services.
- ·Support iPhone, Android, including live video monitoring, playback & two-way audio.
- ·Support CMS(Central Management System)
- ·Back-up to USB storage at the same time when recording

VDH-NXE872

32CH 4M H.265 Network Video Recorder

■ INSTALLATION



- 1. AUDIO Input
- 2. AUDIO Output
- 3. LAN
- 4. HD Output
- 5. VGA Output
- 6. USB
- 7. Alarm Output
- 8. Alarm Input

■ SPECIFICATIONS

| Video | Input | | 32ch 4M |
|----------------|----------------------------------|--------------------------|---|
| | Output | VGA Resolution | VGA |
| | | High Definition(HD) | HDMI |
| Audio | Input | | 1CH Input |
| | Output | | 1CH Output |
| | Audio Compression | | G711A |
| Alarm | Sensor Input | | 16CH Input, Normal Open/ Close |
| | Alarm Output | | Sensor, Motion, Video Loss \ 4CH Output |
| Display | Resolution | | minor streaming from IP CAM |
| | Digital Zoom In | | Drag the Required Area by Mouse |
| | Auto Sequence Duration | | 5-120 seconds Auto Tour |
| Recording | Video Compression | | H.265 |
| and Playback | Resolution | | |
| | Playback | | 32CH 4M |
| | layback | | 9CH 4M Playback |
| | Pacording Mode | | 16CH 1080P Playback |
| | Recording Mode | | Scheduled, Alarm, Manual |
| Dioploy Mard | Event Extension Recording | | 10 ~ 300 sec |
| Display Mode | Data Farmet | | Single / 4 / 8 / 16 / 25 / 32 Split / Tour |
| USB Backup | Data Format | | AVI / use defined format |
| | Media Interface | | USB/Network |
| | Backup Player | | Source Code support and play with Windows Media Playe |
| | | | H.265 |
| Network | Dual Stream | | Minor streaming from IP CAM |
| | Playback | | YES |
| | Communication Protocol | | HTTP · DHCP · DDNS · NTP · SMTP · FTP · DNS · |
| | | | UPNP \ PPPoE \ IP Authorization \ IP Search |
| | Browser | | IE · Firefox · Safari |
| Storage | N | nterface | SATA |
| | | Maximum support capacity | Maximum 8TB HDD |
| | | nternal HDD | 8 pcs |
| | Externa | USB | The port of USB storage device provides simultaneous |
| | | | recording |
| | File System | | Stable and reliable self-developed file system |
| | S.M.A.R.T | | HDD error detecting |
| | Mirror | | Yes |
| UI | Operation Menu | | Graphic Interface; VGA & HD out |
| | Operation Device | | Mouse, Remote (Optional) |
| Port Interface | PTZ & Keyboard | | Pelco-D / Pelco-P (RS-485) |
| Network | Ethernet | | 1*RJ-45 |
| | Web Monitoring | | Real Time Video, Search/Playback, Backup, PTZ, |
| | | | Remote Setting/Update |
| | Daylight Saving Time (DST) | | Yes |
| | Internal Buzzer | | Alarm \ HDD Error \ Motion |
| | Multi Language | | |
| | Firmware Update | | Yes (more than 20 languages) |
| | Network Time Protocol (NTP) | | USB, Network Remote Upgrade |
| | ` ' | | Yes |
| | 3G Mobile Phone | | iPhone, Android supports Live video & audio, |
| | Out of Management 100 ft (2000) | | and playback & way audio. |
| | Central Management Software(CMS) | | Yes |
| General | Operating Environment | | Temperature 0~55°C, Humidity: 20~80% |
| | Power | | Input: 115 / 240VAC, 8 / 4A, 50-60Hz, Output: 350W |
| | Weight | | About 6kg (without HDD and Power Adapter) |
| | Dimension | | 446mm x 367mm x 102mm (W x D x H) |

^{*}Product specifications are subject to change without notice; please contact us for the latest information.



