



ONVIF 2 Megapixel Vandal Dome

IP Camera



NEW 2016 AUG. V1.0



IP Surveillance

VIG-DS751AV

- Sony Exmor 1/2.9" CMOS Image Sensor.
- Real-time H.264,H.265+ ,MJPEG Compression(Dual Codec).
- Resolution : 1920x1080.
- Simultaneous Multiple Streams.
- 30 IR LEDs, IR Range 25M.
- Supports ONVIF Standard to Simplify Integrationand Enhance Interoperability.

VIG-DS751AV

2 Megapixel Vandal Dome IP Camera



SPECIFICATIONS

System	Flash	16MB
	RAM	128MB
Image Sensor	FullHD High Quality 1/2.9" Sony Exmor CMOS Image Sensor	
Sensitivity	0 Lux (IR ON)	
IR LEDs	30PCS	
IR Range	25M	
Lens	Varifocal 2.8-12mm F1.4	
	Removable IR-cut filter for day & night function	
Video	H.264/H.265+ : 1920x1080 @25fps	
	H.264/H.265+ : 1280x720 @30fps	
	H.264/H.265+ : 640x480 @30fps	
	Compression: H.264,H.265+,MJPEG Streaming: Dual Codec (H.264 · H.265+ · JPEG) Selectable	
Image Settings	Support Simultaneous multiple streams	
	Adjustable image size, quality, and bit rate	
	Time/Date stamp and text caption overlay.	
	BNC connector for video output, NTSC/PAL video output switch	
	Configurable brightness, contrast, saturation, sharpness, white balance and exposure	
Networking	AGC / AWB / AES / BLC / WDR	
	Interface	10/100 Mbps Ethernet, RJ-45
	Supported Protocol	IPv4,TCP/IP,DHCP,HTTP,RTSP,SNTP,DNS
	Supported Browser	Microsoft Internet Explorer 6.0 or above
Alarm and Event Managemment	Motion Detection	
	Event notification using SMTP or FTP	
Users	8 clients on-line monitoring at the same time	
	Multi-level user access control with password protection	
Maintenance	Supports online firmware upgrade	
I/O	RJ-45 Ethernet x 1,DC Jack x1	
Power	DC12V or PoE IEEE802.3af Class 0 (optional)	
Max. Power Consumption	3.6W(IR OFF),7W(IR ON)	
Weight	Netweight: 1050g	
Dimension	W:Φ150mm H:110mm	
Operating Environments	Temperature: 0 ~ 45 °C , Humidity: 90%	

★Product specifications are subject to change without notice; please contact us for the latest information.



■ DISTRIBUTED BY

