



ONVIF 2 Megapixel IR Bullet

IP Camera



NEW 2016 AUG. V1.0



IP Surveillance
VIG-US733A

- Sony Exmor 1/2.9" CMOS Image Sensor.
- Improved low-light performance.
- Real-time H.264,H.265+, MJPEG Compression(Dual Codec).
- Resolution : 1920x1080.
- Simultaneous Multiple Streams.
- 24 IR LEDs, IR range 20M
- Supports ONVIF Standard to Simplify Integrationand Enhance Interoperability.

VIG-US733A 2 Megapixel IR Bullet IP Camera



SPECIFICATIONS

| | | |
|----------------------------|---|---|
| System | Flash : 16MB | |
| | RAM : 128MB | |
| Image Sensor | FullHD High Quality 1/2.9" Sony Exmor CMOS Image Sensor | |
| Sensitivity | 0 Lux (IR ON) | |
| IR LEDs | 24PCS | |
| IR Range | 20M | |
| Lens | Board Lens 3.6mm F1.8 | |
| | Removable IR-cut filter for day & night function | |
| Video | H.264/H.265+ : 1920x1080 @25fps | |
| | H.264/H.265+ : 1280x720 @30fps | |
| | H.264/H.265+ : 640x480 @30fps | |
| | Compression: H.264, H.265+, MJPEG Streaming: Dual Codec (H.264 · H.265+ · JPEG) Selectable Support Simultaneous multiple streams | |
| Image Settings | Adjustable image size, quality, and bit rate | |
| | Time/Date stamp and text caption overlay. | |
| | Configurable brightness, contrast, saturation, sharpness, white balance and exposure | |
| | AGC / AWB / AES / BLC / WDR | |
| Networking | Interface | 10/100 Mbps Ethernet, RJ-45 |
| | Supported Protocol | IPv4, TCP/IP, DHCP, HTTP, RTSP, SNTP, DNS |
| | Supported Browser | Microsoft Internet Explorer 6.0 or above |
| Alarm and Event Management | Motion Detection | |
| | Event notification using SMTP or FTP | |
| Users | 8 clients on-line monitoring at the same time | |
| | Multi-level user access control with password protection | |
| Maintenance | Supports online firmware upgrade | |
| I/O | RJ-45 Ethernet x 1, DC Jack x1 | |
| IP Rating | IP66 | |
| Power | DC12V or PoE IEEE802.3af Class 0 (optional) | |
| Max. Power Consumption | 3.6W(IR OFF), 7W(IR ON) | |
| Weight | Netweight: 850g | |
| Dimension | 263.5 × 80 × 77.7 mm | |
| Operating Environments | Temperature: 0 ~ 45 °C | Humidity: 90% |

★ Product specifications are subject to change without notice; please contact us for the latest information.



■ DISTRIBUTED BY

