

VDN-DKF608D 5MP

8CH Network Video Recorder





















- > Pentaplex Operation: which can Record / Playback / Remote Connection / mobile phone watch
- > single hard drive can be up to 8TB.
- > Support HD output
- > Support IE. On-line recording/playback and user management are available.
- > Support HTTP, DHCP, DDNS, NTP, SMTP, FTP, DNS, UPNP, PPPoE, IP rights, IP search and other Internet services.
- > Support iPhone, Android, including live video monitoring, playback.
- > Support CMS(Central Management System).
- > Back-up to USB storage at the same time when recording.
- > Various modes supported, both analog & digital IP signal can be connected to DVR as hybrid features.
- > With P2P function, scan QR-Code on the smartphone app to get instant monitoring and playback, and high information security
- > Set DVR on IPCAM mode to get an auto connection on Fuho plug-n-play IP Cam.
- > Support WiFi, 4G network.
- > Support for automatic firmware updates
- > Supporting AHD, CVI, TVI, CVBS, and digital IP signals.

VDN-DKF608D Detailed Information

SPECIFICATIONS

Video Input- BNC

Video Output- VGA Resolution

High Definition(HD)

Audio Input- 1CH Input

Audio Output- 1CH Output

Audio Compression- G.711U

Resoluation- 1080P

Digital Zoom- Area selected by mouse dragging

Auto Sequence Duration- YES

Recording Video Compression- H.265

Frame- 8CH 5M @6fps/CH;

8CH 1080P @15fps/CH;

Recording Mode- Continuous/ Schedule/ Motion

Motion Detection- Zones: 192(16×12 grid)

Pre-Record- 1-5 sec

Post-Recording- 10 ~ 300 sec

Display Mode- Single, Quad, Sequence

File Format- MP4

Media Interface- USB/Network

Playback- YES

Communication Protocol- HTTP \ DHCP \ DDNS \ NTP \ SMTP \ FTP \ DNS \

UPNP \ PPPoE \ IP Authority \ IP Search

Browser- IE

Storage HDD Interface- SATA

Maximum support capacity- Maximum 8TB HDD

Internal HDD- 1 pcs

File System- Stable and reliable self-developed file system

S.M.A.R.T- HDD error detecting

Version updating is not going to inform, please check the on-going updating information



Distributed BY

VDN-DKF608D Detailed Information

SPECIFICATIONS

Menu Display- GUI interface ; VGA & HD & CVBS outsimultaneously

Input Method- Mouse

Ethernet- 1*RJ-45, 10/100 Base-T

Web Monitoring- Live, Search/Playback, Backup, PTZ,

Remote Setup/Upgrade

Internal Buzzer- Beep warning sound on system start

Multi Language- English, Simplified Chinese, Traditional Chinese,

Japanese

Firmware Update- USB, Network Remote Upgrade

Network Time Protocol (NTP)- Yes

Mobile Phone- iPhone, Android, Mobile App supports Live video &

audio, and playback.

Central Management Software(CMS)- Yes

Hybrid(Digital & Analogue)- Yes

Operating Environment- Temperature 0~46°C, Humidity: 20~80%

Power- DC 12V / 3A(AC100V~240V 50/60HZ)

Weight- About 3kg (without HDD and Power Adapter)

Dimension- 430mm x 314mm x 53mm (W x D x H)

Version updating is not going to inform, please check the on-going updating information



Distributed BY