


VDN-DKF608E 5MP

8CH video recording system



- › Multitasking: which can Record / Playback / Remote Connection / Mobile phone watch and playback at the same time.
- › The maximum supporting capacity for a single hard disk is 10 TB.
- › Support HD ultra high definition output.
- › It supports remote IE browsing, monitor live footage, and playback simultaneously.
- › Provide HTTP, DHCP, DDNS, NTP, SMTP, FTP, DNS, UPNP, PPPoE, and IP authority services.
- › Support iPhone, Android video monitoring and playback.
- › It supports CMS (Central Management System).
- › It can be set as a Hybrid function to connect traditional analog signals and digital IP signals at the same time and the IP channel can be set at will.
- › With P2P function, scan QR-Code through APP for real-time monitoring and playback to increase information security.
- › Set the IP CAM mode on the host, and use FUHO IP Cam to plug and play.
- › Applicable for VACRON IP cam with no extra operation or settings other than plugging.
- › Applicable for ONVIF IP cam.
- › Applicable for RTSP IP cam.
- › Supports VACRON recording devices.
- › Support automatic update.
- › It supports AHD, TVI, CVI, CVBS, and IP signal inputs.

SPECIFICATIONS

Video input-	8 CH of BNC input
Video output-	VGA output (Max. 1920x1080) HD OUT output (Max. 3840x2160)
Audio input-	4CH RCA input (could extend to 8CH audio)
Audio output-	1CH RCA output
Alarm input-	4 inputs, normally open/normally closed (optional)
Alarm output-	1 alarm output(optional)
Audio Compression-	G.711U

Digital Zoom in-	Yes
Sequence-	Yes
Video Compression-	H.264/H.265
Recording Frame-	8CH 5MP @6FP S/CH : 8CH 1080P @15FP S/CH :
Recording Mode-	Continuous, Scheduled, Displacement
Motion Detection-	Zones: 192(16×12 grid)
Playback-	Video playback up to 1 channel 5MP@6 FPS/sec, or 1 channel 1080P@15 FPS/sec or 8 channel VGA
Display Mode-	Single Screen/ 4-Split/ 9-Split/ Sequence
Backup File Format-	MP4/self-defined format
Backup File Method-	USB/ WEB
Network Services-	HTTP, DHCP, DDNS, NTP, SMTP, FTP, DNS, UPNP, PPPoE, IP authority

Version updating is not going to inform, please check the on-going updating information

SPECIFICATIONS

Network Connection- Live View, Search/Playback, Backup, and Update

Browser- IE, WEB-Client

HDD Storage Interface- SATA x2

Maximum Supported Capacity- 10TB per unit

Network Socket- RJ-45 x1, 10/100/1000 Base-T

USB- front plate USB2.0x1 / black plate USB2.0x1

File System- Stable and reliable self-developed file system

S.M.A.R.T- HDD error detecting

Port- RS-485 (Pelco-D / Pelco-P)

Operation menu- Graphical User Interface (GUI);
Supports simultaneous display on VGA, HD out, and CVBS

Input method- Mouse

Internal Buzzer- Start-up Beep

Languages- English / Simple Chinese/ Traditional Chinese/ Japanese

Firmware Update- USB update or Network Update(OTA)

APP Monitoring- iPhone, Android, Mobile App supports Live view& audio,
playback and back-up

CMS (Central Management System)- Supports

Hybrid(Digital & Analog)- Supports

Operating Environment- Temperature 0~+46°C, Humidity: 20~80%

Power Supply- DC 12V / 4A(AC100V~240V 50/60HZ)

Net weight- About 2.7 kg (without HDD and Power Adapter)

Dimensions- 430mm x 314mm x 53mm (L×W×H)

Version updating is not going to inform, please check the on-going updating information