

VDN-DKF616D 5MP

16CH Network Video Recorder



















- > Pentaplex Operation: which can Record / Playback / Remote Connection / mobile phone watch
- > Hard Drive support 10TB
- > Support HD video output
- > Support MS IE11 for live monitor and playback function
- > Support HTTP、DHCP、DDNS、NTP、SMTP、FTP、DNS、UPNP、PPPoE、IP search ..etc network protocol
- > Support Iphone and Android for live monitoring and playback
- > CMS support for Effectively integrate device management operations
- Various modes supported , both analog & digital IP signal can be connected to DVR as hybrid features.
- > With P2P function, scan QR-Code on the smartphone app to get instant monitoring and playback, and high information security
- > Set DVR on IPCAM mode to get an auto connection on Fuho plug-n-play IP Cam.
- > Support 4G network
- > Support for automatic firmware updates
- > Supporting AHD, CVI, TVI, CVBS, and digital IP signals

VDN-DKF616D Detailed Information

SPECIFICATIONS

Video Input- 16CH Input BNC

Video Output- VGA Resolution(Max. 1920x1080)

High Definition(HD)(MAX. 3840x2160)

Audio Input- 4 ch input

Audio Output- 1 ch output

Audio Compression- G.711U

Alarm input- 4 alarm input , relay (optional)

Alarm Output- 1 alarm input, replay (optional)

Display Resolution- 1080P

Digital Zoom- Area selected by mouse dragging

Auto Sequence Duration- Yes

Video Compression- H.265

Recording Frame- 16 CH 5MP @6FPS/CH

16CH 1080P @30FPS/CH

Recording Mode- Continuous / Schedule / Motion

Motion Detection- Zones: 192(16×12 grid)

Pre-Record- 1-30 second

Post-Recording- 10-300 second

Display Mode- Single, Quad, 8-Split, 9-Split, 16-Split, Sequence

File Format- MP4

Media Interface- USB/Network

Playback- Yes

Network Protocol- HTTP \ DHCP \ DDNS \ NTP \ SMTP \ FTP \ DNS \

UPNP \ PPPoE \ IP Authority \ IP Search

Browser- IE

Storage HDD Interface- SATA

Maximum support capacity- Maximum 10TB HDD

Internal HDD- 2 pcs

Version updating is not going to inform, please check the on-going updating information



Distributed BY

VDN-DKF616D Detailed Information

SPECIFICATIONS

File System- stable and reliable self-developed file system

S.M.A.R.T- HDD error detecting

Menu Display- GUI interface ; VGA & HD out simultaneously

Input Method- Mouse

PTZ and joy keyboard- Pelco-D / Pelco-P (RS-485)

Network Ethernet- RJ-45 *1

Web Monitoring- Live, Search/Playback, Backup, Upgrade, PTZ

Internal Buzzer- Bee at power on

Language- English / Simp Chinese/ Traditional Chinese/

Japanese

Firmware Update- USB, Network Remote Upgrade

Mobile Surveillance- iPhone, Android, Mobile App supports Live video

& audio, and playback.

Central Management Software(CMS)- Support

Hybrid(Digital & Analogue) - Support

Operating Environment- Temperature 0~+46°C, Humidity: 20~80%

Power- DC 12V / 4.17A(AC100V~240V 50/60HZ)

Net weight- About 3kg (without HDD and Power Adapter)

Dimension- 430mm x 314mm x 53mm (W x D x H)

Version updating is not going to inform, please check the on-going updating information



Distributed BY