

VDN-DKN604D 5MP

4CH Video & Audio Recording System



- › Multitasking for recording/playback/remote connection/ backup/mobile phone monitoring and playback simultaneously.
- › A single hard drive capacity up to 8TB is supported.
- › Support HD output.
- › Remote Access through Internet Explorer (IE) browsing with video monitoring and playback.
- › Support HTTP, DHCP, DDNS, NTP, SMTP, FTP, DNS, UPNP, PPPoE, IP rights, IP search and other network services.
- › Support iPhone and Android video & audio monitoring and playback.
- › Support CMS (Central Management System).
- › The Hybrid function can be configured to connect traditional analog signals and digital IP signals at the same time, as well as to free set channel for IP.
- › With P2P function, scan QR-Code through APP for real-time monitoring and playback to increase information security.
- › Set the host device for IP-CAM mode. Plug and start using FUHO IP-CAM.
- › Support automatic updates.
- › Support AHD, TVI, CVI, CVBS, and IP signal inputs.

SPECIFICATIONS

Video Input-	4 BNCs
Video Output-	VGA (Max. 1920×1080) HD (Max. 1920×1080) CVBS
I/O Interface-	RJ-45*1, 10 / 100 Base-T USB2.0*2
Audio Input-	1-CH Input
Audio Output-	1-CH Output
Sound Compression-	G.711U
<hr/>	
Display Resolution-	1080P
Digital Zoom in-	Drag and drop to enlarge.
Sequencing-	YES
Image Compression Method-	H.264 / H.265
Record FPS-	4CH 5MP @6FPS/CH ; 4CH 1080P @15FPS/CH ;
Recording Mode-	Continuity, Scheduling, Motion
Motion Detection-	Grid setting, 192(16*12) detection zones can be set.
Display Mode-	Single Screen / 4 Split / 9 Split / sequence
File Format-	MP4 / Self-Defined Format
Media Interface-	USB / Network
Remote Playback-	YES
Network Services-	HTTP, DHCP, DDNS, NTP, SMTP, FTP, DNS, UPNP, PPPoE, IP Privilege, IP search
Browser-	Internet Explorer (IE)
Web Monitor-	Live View Search/Playback, Backup, and Update
Storing Hard Disk Interface-	SATA
Max. Supported Capacity-	Maximum 8TB per unit

Specifications are subject to change without prior notice.

SPECIFICATIONS

Number of Internal Hard Disk Drives-	1 unit
File System-	Stable and Reliable Self-Developed File System
S. M. A. R. T.-	Hard Disk Error Check
Operation Menu-	Graphic Interface VGA, HD out & CVBS can be displayed at the same time.
Input Method-	Mouse

Internal Buzzer-	Start-up Beep
Languages-	English, Simplified Chinese, Traditional Chinese, Japanese
Firmware Update-	USB Update ; Network Update(OTA)
APP Monitoring-	iPhone & Android support monitoring (with audio) and playback.

Central Monitoring Video

Management System (CMS)-	Support
Hybrid Function (Digital & Analog)-	Support
Operating Environment-	0~46°C, 20~80% Humidity
Power-	DC 12V / 3A (AC100V~240V 50/60HZ)
Net Weight (Gross Weight)-	Approx. 1kg (without HDD & Power Adapter)
Dimensions-	270mm×200mm×80mm (L×W×H)

Specifications are subject to change without prior notice.