

## VDN-DKN608D 5MP

## 8CH Digital Video Recording System





- > Pentaplex Operation: which can Record / Playback / Remote Connection / mobile phone watch
- > single hard drive can be up to 8TB.
- > Support HD output
- > Support IE. On-line recording/playback and user management are available.
- Support HTTP, DHCP, DDNS, NTP, SMTP, FTP, DNS, UPNP, PPPoE, IP rights, IP search and other Internet services.
- > Support iPhone, Android, including live video monitoring, playback.
- > Support CMS(Central Management System).
- > Back-up to USB storage at the same time when recording.
- Various modes supported , both analog & digital IP signal can be connected to DVR as hybrid features.
- > With P2P function, scan QR-Code on the smartphone app to get instant monitoring and playback, and high information security
- Set NVR on IPCAM mode to get an auto connection on Fuho plug-n-play IP Cam.
- > Support WiFi, 4G network.
- > Support for automatic firmware updates
- Supporting AHD, CVI, TVI, CVBS, and digital IP signals.

## SPECIFICATIONS

Video Input-	4CH Input / BNC(1Vp-p 75Ω)
Video Output-	VGA Resolution
	High Definition(HD)
Audio Input-	1CH Input
Audio Output-	1CH Output
Audio Compression-	G.711U

Resoluation-	1080P
Digital Zoom-	Area selected by mouse dragging
Auto Sequence Duration-	YES
Video Compression-	H.265
Frame-	8CH 5M @6fps/CH ;
	8CH 1080P @15fps/CH ;
Recording Mode-	Continuous/ Schedule/ Motion
<b>Motion Detection-</b>	Zones: 192(16×12 grid)
Pre-Record-	1-5 sec
Post-Recording-	10 ~ 300 sec
Display Mode-	Single, Quad, Sequence
File Format-	MP4
Media Interface-	USB/Network
Playback-	YES
<b>Communication Protocol-</b>	HTTP 、 DHCP 、 DDNS 、 NTP 、 SMTP 、 FTP 、
	DNS \ UPNP \ PPPoE \ IP Authority \ IP Search
Browser-	IE
Storage HDD Interface-	SATA
Maximum support capacity-	Maximum 8TB HDD

Version updating is not going to inform, please check the on-going updating information

## SPECIFICATIONS

Internal HDD-	1 pcs
File System-	Stable and reliable self-developed file system
S.M.A.R.T-	HDD error detecting
Menu Display-	GUI interface;VGA & HD & CVBS outsimultaneously
Input Method-	Mouse
Ethernet-	1*RJ-45, 10/100 Base-T
Web Monitoring-	Live, Search/Playback, Backup, PTZ,
	Remote Setup/Upgrade
Internal Buzzer-	Beep warning sound on system start
Multi Language-	English, Simplified Chinese, Traditional Chinese,
	Japanese
Firmware Update-	USB, Network Remote Upgrade
Network Time Protocol (NTP)-	Yes
Mobile Phone-	iPhone, Android, Mobile App supports Live video &
	audio, and playback.
Central Management Software(CMS)-	Yes
Hybrid(Digital & Analogue)-	Yes
<b>Operating Environment-</b>	Temperature 0~46°C, Humidity: 20~80%
Power-	DC 12V / 3A(AC100V~240V 50/60HZ)
Weight-	About 1kg ( without HDD and Power Adapter)
Dimension-	200mm x 276mm x 80mm (W x D x H)
Central Management Software(CMS)- Hybrid(Digital & Analogue)- Operating Environment- Power- Weight-	audio, and playback. Yes Yes Temperature 0~46°C, Humidity: 20~80% DC 12V / 3A(AC100V~240V 50/60HZ) About 1kg ( without HDD and Power Adapter)

Version updating is not going to inform, please check the on-going updating information

