


VDN-DKN608E 5MP

8CH video recording system



- › Multitasking: which can Record / Playback / Remote Connection / Mobile phone watch and playback at the same time.
 - › The maximum supporting capacity for a single hard disk is 10 TB.
 - › Support HD ultra high definition output.
 - › It supports remote IE browsing, monitor live footage, and playback simultaneously.
 - › Provide HTTP, DHCP, DDNS, NTP, SMTP, FTP, DNS, UPNP, PPPoE, and IP authority services.
 - › Support iPhone, Android video monitoring and playback.
 - › It supports CMS (Central Management System).
 - › It can be set as a Hybrid function to connect traditional analog signals and digital IP signals at the same time and the IP channel can be set at will.
- With P2P function, scan QR-Code through APP for real-time monitoring and playback to
- › increase information security.
 - › Set the IP CAM mode on the host, and use FUHO IP Cam to plug and play.
 - › Applicable for VACRON IP cam with no extra operation or settings other than plugging.
 - › Applicable for ONVIF IP cam.
 - › Applicable for RTSP IP cam.
 - › Supports VACRON recording devices.
 - › Support automatic update.
 - › It supports AHD, TVI, CVI, CVBS, and IP signal inputs.

SPECIFICATIONS

Video input-	8 CH of BNC input
Video output-	VGA output (Max. 1920x1080) HD OUT output (Max. 1920x1080)
Audio input-	4CH RCA input
Audio output-	1CH RCA output
Audio Compression-	G.711U
<hr/>	
Digital Zoom in-	Yes
Sequence-	Yes
Video Compression-	H.264/H.265
Recording Frame-	8CH 5MP @6FP S/CH ; 8CH 1080P @15FP S/CH
Recording Mode-	Continuous, Scheduled, Displacement
Motion Detection-	Zones: 192(16×12 grid)
Playback-	Video playback up to 1 channel 5MP@6 FPS/sec, or 1 channel 1080P@15 FPS/sec or 8 channel VGA
Display Mode-	Single Screen/ 4-Split/ 9-Split
Backup File Format-	MP4/self-defined format
Backup File Method-	USB/ WEB
Network Services-	HTTP, DHCP, DDNS, NTP, SMTP, FTP, DNS, UPNP, PPPoE, IP authority
Network Connection-	Live View, Search/Playback, Backup, and Update
Browser-	IE, WEB-Client

Version updating is not going to inform, please check the on-going updating information

SPECIFICATIONS

HDD Storage Interface-	SATA x2
Maximum Supported Capacity-	10TB per unit
Network Socket-	RJ-45 x1 (10/100 Base-T)
USB-	front plate USB2.0x1 / black plate USB2.0x1
File System-	Stable and reliable self-developed file system
S.M.A.R.T-	HDD error detecting
Port-	RS-485 (Pelco-D / Pelco-P)
Operation menu-	Graphical User Interface (GUI); Supports simultaneous display on VGA, HD out
Input method-	Mouse
Internal Buzzer-	Start-up Beep
Languages-	English / Simple Chinese/ Traditional Chinese/ Japanese
Firmware Update-	USB update or Network Update(OTA)
APP Monitoring-	iPhone, Android, Mobile App supports Live view& audio, playback and back-up
CMS (Central Management System)-	Supports
Hybrid(Digital & Analog)-	Supports
Operating Environment-	Temperature 0~+46°C, Humidity: 20~80%
Power Supply-	DC 12V / 4A(AC100V~240V 50/60HZ)
Net weight-	About 1 kg (without HDD and Power Adapter)
Dimensions-	275mm x 200mm x 80mm (L×W×H)

Version updating is not going to inform, please check the on-going updating information