

# VDN-DKS604ES 5MP

## 4CH AV recording system



- > Multitasking: which can Record / Playback / Remote Connection / mobile phone watch at the same time.
- > Hard Drive supports 2.5 inches SSD 1TB
- > Support HD ultra high definition output.
- > It supports remote IE browsing, monitor live footage and playback simultaneously.
- > Support HTTP, DHCP, DDNS, NTP, SMTP, FTP, DNS, UPNP, PPPoE, IP authority, IP search and other network services
- > Support iPhone, Android video monitoring and playback
- > CMS support for effectively integrate device management operations
- > It can be set as a hybrid system, allows simultaneous connections for both traditional analog signals and digital IP signals.
- > With P2P function, scan QR-Code through APP for real-time monitoring and playback to increase information security.
- > Set the IPCAM mode on the host, and use FUHO IPCAM to plug and play
- > It supports AHD, TVI, CVI, CVBS, and IP signal inputs.

## SPECIFICATIONS

---

<b>video input-</b>	4 sets of BNC
<b>video output-</b>	HD out (Max. 1920x1080)
<b>I/O Interface-</b>	RJ-45 *1, 10/100 Base-T USB2.0*2
<b>Resolution-</b>	1080P
<b>Digital zoom-</b>	Yes
<b>sequence-</b>	5 seconds Auto-Seq

---

<b>Image Compression-</b>	H.264/H.265
<b>Motion Detection-</b>	Under 1080P@15 frames per second mode, it can achieve real-time monitoring of 1 channel. Or under 5MP@6 frames per second mode, it can achieve real-time monitoring of 1 channel. Or 4 channels of real-time monitoring in VGA resolution.
<b>Recording Mode-</b>	Continuous / Schedule / Motion
<b>Motion Detection-</b>	Zones: 192(16×12 grid)
<b>Playback-</b>	Video playback up to 1 channel 5MP@6 frames per second or 1 channel 1080P@15 frame/second or 4 channel VGA playback
<b>Display Mode-</b>	Single Screen/4-Split/Sequence
<b>Backup file format-</b>	MP4 / Self-Defined Format
<b>Media interface-</b>	USB / Network
<b>Network Playback-</b>	yes
<b>Network Protocol-</b>	HTTP, DHCP, DDNS, NTP, SMTP, FTP, DNS, UPNP, PPPoE, IP authority, IP search
<b>Browser-</b>	IE
<b>Web-</b>	Live view, search/playback, backup, remote configuration/update

---

Specifications are subject to change without prior notice.

## SPECIFICATIONS

---

**Storage HDD Interface-** SATA

**Maximum support capacity-** Supports 2.5 inches SSD 1TB

**Number of internal hard drives-** 1 piece

**file system-** Stable and reliable self-developed file system

**S.M.A.R.T-** Hard Disk Error Check

**Operation Menu-** GUI interface : HD out

**input method-** Mouse

---

**Daylight saving time DST-** Yes

**Multilingual-** English / Simple Chinese/ Traditional Chinese/ Japanese

**software update-** USB update , network update(OTA)

**Network Time Protocol-** Yes

**APP monitoring** iPhone, Android, mobile App supports live view(includes audio) and playback.

**CMS (Central Management System)-** support

**Hybrid (Digital & Analog)-** support

**Operating Environment-** Celsius 0 ~ 50°C , humidity 10~90%

**Power Supply-** DC 5V / 2A(AC100V~240V 50/60HZ)

**Net weight-** About 0.5kg (including HDD but excluding poweradapter)

**Dimension-** 216mm x 97mm x 43mm (Length x Width x Height)

---

Specifications are subject to change without prior notice.