

VDN-DKZ604D 5MP

4CH Digital Video Recorder



- › Pentaplex Operation: which can Record / Playback / Remote Connection / mobile phone watch
Hard Drive support 8TB
- › Support HD video output
- › Support MS IE11 for live monitor and playback function
- › Support HTTP、DHCP、DDNS 、NTP 、SMTP 、FTP 、DNS 、UPNP 、PPPoE 、IP search, and other network protocol
- › Support iPhone and Android for live monitoring and playback
CMS support for Effectively integrate device management operations
- › Various modes supported , both analog & digital IP signal can be connected to DVR as hybrid features.
- › With P2P function, APP can scan QR-Code for real-time monitoring and playback, increasing information security
- › Set the IPCAM mode on the host, and use FUHO IPCAM to plug and play.
- › Support WIFI network
- › Support automatic update
- › Support AHD, TVI, CVI, CVBS, IP signal input

SPECIFICATIONS

Video Input-	4 groups of BNC(1Vp-p 75Ω)
Video Output-	VGA Resolution High Definition(HD) CVBS
Audio Input-	1 ch input
Audio Output-	1 ch output
Audio Compression-	G.711U

Display Resolution-	1080P
Digital Zoom-	Yes
platform-	5 seconds automatic platform jump
Video Compression-	H.265
Recording Frame-	4CH 5M @6fps/CH; 4CH 1080P @15fps/CH;
Recording Mode-	Continuous / Schedule / Motion
Motion Detection-	Zones: 192(16×12 grid)
Display Mode-	Single, Quad, Sequence
File Format-	MP4/Custom Format
Media Interface-	USB/Network
Playback-	Yes
Network Protocol-	HTTP 、 DHCP 、 DDNS 、 NTP 、 SMTP 、 FTP 、 DNS 、 UPNP 、 PPPoE 、 IP Authority 、 IP Search
Browser-	IE
Storage HDD Interface-	SATA
Maximum support capacity-	Maximum 8TB HDD
Internal HDD-	1 pcs

Specifications are subject to change without prior notice.

SPECIFICATIONS

External storage- Support real-time synchronous recording of USB storage devices

File System- stable and reliable self-developed file system

S.M.A.R.T- HDD error detecting

Menu Display- GUI interface : VGA & HD out& CVBS simultaneously

Input Method- Mouse

Network Ethernet- 1*RJ-45, 10/100 Base-T

Web Monitoring- Live, Search/Playback, Backup, Remote setup, Upgrade

Daylight Saving Time(DST)- Yes

Multi-lingual- Yes,(more than 20 languages)

Firmware Update- USB and Network Remote Upgrade

Network Time Protocol- Yes

4G Mobile Phone Monitoring- iPhone, Android,
Mobile App supports Live video& audio,and playback.

Central Management Software(CMS)- Support

Hybrid(Digital & Analogue)- Support

Operating Environment- Celsius 0 ~ 50°C, humidity 10~90%

Power Supply- DC 12V / 3A(AC100V~240V 50/60HZ)

Net weight- About 0.5kg (without HDD and Power Adapter)

Dimension- 255mm x 216mm x 42mm (L x W x H)

Specifications are subject to change without prior notice.