


VDN-NKE836D 5MP

Cybersecurity Certification

36CH Network Video Recording System



- › Pentaplex Operation: which can Record / Playback / Remote Connection / mobile phone watch
- › Single hard drive can be up to 10TB.
- › Support HD output
- › Support IE. On-line recording/playback and user management are available.
- › Support HTTP、DHCP、DDNS、NTP、SMTP、FTP、DNS、UPNP、PPPoE、IP search ..etc network protocol
- › Support iPhone, Android, including live video monitoring, playback.
- › CMS support for Effectively integrate device management operations
- › It has P2P functionality, and the APP allows real-time monitoring and playback by scanning a QR-Code, enhancing information security.
- › Applicable for ONVIF IP cam
- › Applicable for RTSP IP camera
- › Supports VACRON recording devices
- › Supports automatic updates.

SPECIFICATIONS

Video input- 36CH 5MP (RJ45 input)

Video output- VGA output (Max.1920x1080)
HD OUT output (Max. 3840 x 2160)

Audio Compression- G.711U

Digital Zoom in- YES

Sequence- YES

Video Compression- H.264/H.265

Recording Frame- VGA @30FPS/sec. up to 36 CH Monitoring
1-channel real-time video monitoring
in 5MP@15 FPS/sec.

Recording Mode- Continuous, Scheduled, Displacement

Motion Detection- Zones: 192(16×12 grid)

Playback- Video playback up to
1 channel 5MP@10 frames per second
1 channel 1080P@30 FPS/sec
36 channel VGA at 30 FPS

Display Mode- Single, Quad, 9-Split, 13-Split, 16-Split,
25-Split, 36-Split

Backup File Format- MP4/Self-defined format.

Backup File Method- USB / WEB

Network Services- HTTP、DHCP、DDNS、NTP、SMTP、FTP、DNS、
DNS、UPNP、PPPoE、IP Authority、IP Search

Network Connection- Live View, Search/Playback, Backup, and Update

Browser- IE / WEB-Client

HDD Storage Interface- (1) SATA x4
(2) SATA x8

Version updating is not going to inform, please check the on-going updating information

SPECIFICATIONS

Maximum Supported Capacity- 10TB per unit

Network Socket- RJ-45x1 (10/100/1000 Base-T)

USB- Front late USB2.0*1
Black plate USB2.0x1 + USB3.0x1

File System- Stable and Reliable Self-Developed File System

S.M.A.R.T- Hard Disk Error Check.

Operation menu- GUI interface : VGA & HD out can be displayed simultaneously

Input method- Mouse.

Internal Buzzer- Initiate beep at power on

Languages- English, Traditional Chinese, Simplified Chinese, Japanese

Firmware Update- USB update or Network Update(OTA)

APP Monitoring- iPhone, Android, Mobile App supports
Live view& audio, playback and back-up.

CMS

(Central Management System)- Support

Operating Environment- Temperature 0~+46°C, Humidity: 20~80%

Power Supply- (1) DC 12V / 6A(AC100V~240V 50/60HZ)
(2) AC 115 / 230VAC, 8/4A, 50-60Hz, Output:400W

Net weight- About 4.2kg (excluding HDD and Power Adapter)

Dimensions- 445mm x 370mm x 97mm (L x W x H)

Version updating is not going to inform, please check the on-going updating information