


VDN-NKE836E 5MP

36CH Network Video Recording System



- › Multitasking, it can record / playback / remote connection / mobile phone watch and playback simultaneously.
- › The maximum supporting capacity for a single hard disk is 10 TB.
- › It supports HD ultra high definition output.
- › It supports remote IE browsing, monitor live footage, and playback simultaneously.
- › Provide HTTP, DHCP, DDNS, NTP, SMTP, FTP, DNS, UPNP, PPPoE, and IP authority services.
- › It supports iPhone, Android video monitoring and playback.
- › It supports CMS (Central Management System).
- › With the P2P function, scan the QR code through the APP for real-time monitoring and playback to increase information security.
- › Applicable for VACRON IP cam with no extra operation or settings than plugging.
- › Applicable for ONVIF IP cam
- › Applicable for RTSP IP cam
- › Supports VACRON recording device
- › Supports automatic update

SPECIFICATIONS

Video input-	36CH 5MP (RJ45 input)
Video output-	VGA output (Max. 1920x1080) HD OUT output (Max. 3840 x 2160)
Audio Compression-	G.711U
Digital Zoom in-	Yes
Sequence-	Yes
Video Compression-	H.264/H.265
Recording Frame-	VGA @30FPS/sec. up to 36 CH Monitoring 1-channel real-time video monitoring in 5MP@10 FPS/sec.
Recording Mode-	Continuous, scheduled, displacement
Motion Detection-	Zones: 192(16×12 grid)
Playback-	Video playback up to 1 channel 5MP@10 frames per second, or 1 channel 1080P@30 FPS/sec, or 36 channel VGA@30 FPS/sec.
Display Mode-	Single, Quad, 9-Split, 13-Split, 16-Split, 25-Split, 36-Split
Backup File Format-	MP4/self-defined format
Backup File Method-	USB/ WEB
Network Services-	HTTP, DHCP, DDNS, NTP, SMTP, FTP, DNS, UPNP, PPPoE, IP authority
Network Connection-	Live View Search/Playback, Backup, and Update
Browser-	IE / WEB-Client

Version updating is not going to inform, please check the on-going updating information

SPECIFICATIONS

HDD Storage Interface- (1) SATA x4

(2) SATA x8

Maximum Supported Capacity- 10TB per unit

Network Socket- RJ-45*1 (10/100/1000 Base-T)

USB- front plate USB2.0x1 / black plate USB2.0x1 + USB3.0x1

File System- Stable and reliable self-developed file system

S.M.A.R.T- Hard Disk Error Check

Operation Menu- GUI interface : VGA & HD out simultaneously

Input Method- Mouse

Internal Buzzer- Start-up Beep

Languages- English / Simple Chinese/ Traditional Chinese/ Japanese

Firmware Update- USB update or Network Update(OTA)

APP Monitoring- iPhone, Android, Mobile App supports Live view& audio, playback and back-up.

CMS(Central Management System)- Supports

Operating Environment- Temperature 0~+46°C, Humidity: 20~80%

Power Supply- (1) DC 12V / 6A(AC100V~240V 50/60HZ)
(2) AC 115/230VAC, 8/4A, 50-60Hz, Output:400W

Net Weight- Approx. 4.2kg (without HDD & Power Adapter)

Dimensions- 430mm x 370mm x 97mm (L×W×H)

Version updating is not going to inform, please check the on-going updating information