

VID-DS758-D6 5MP

Indoor IP Camera



- › Sony 5MP 1/2.8" COMS Image Sensor
- › Real-time H.265/H.264/MJPEG Compression(dual codec)
- › Highest Resolution 2592*1944 @ 15fps/s
- › HI-P 3 LED, IR Distance 15M
- › Wider monitoring range up to 160° horizontal view angle
- › Support ONVIF international standard, best compatibility and integration

SPECIFICATIONS

system- Flash : 16MB
RAM : 256MB

Image Sensor- Full HD High Quality 1/2.8" CMOS Image Sensor

Lens- Board Lens 2.0 mm

IR-cut- Removable IR-cut filter for day & night function

Low Lux- 0 .01Lux

LED- HI-P 3 IR LED

Compression- H.265+: 2560x1920 at 15fps
H.265+: 2048x1536 at 20 fps
H.265+: 1920x1080 at 30fps
H.265 、 H.264 、 JPEG Multi-mode
compression (Dual Codec)

Support Simultaneous multiple streams

Image Settings- Adjustable image size,quality, and bit rate
Time/Date stamp and text caption overlay
Configurable brightness, contrast, saturation,
sharpness, white balance and exposure
Have: AGC 、 AWB 、 AES 、 BLC 、 WDR Features

Electronic Shutter- 1/2 ~ 1/100,000 Sec

Networking Interface- 10 /100 Mbps,RJ-45

Protocol- IPv4,TCP/IP, DHCP, HTTP, RTSP,SNTP,DNS

browser- Microsoft Internet Explorer 6.0 or above

Safari, Chrome or Firefox

Alarm and Event Management- Motion Detection

Event notification using SMTP or FTP

Version updating is not going to inform, please check the on-going updating information

SPECIFICATIONS

- Users-** clients on-line monitoring at the same time
Multi-level user access control with password protection
- Maintenance-** Supports online firmware upgrade
- I/O-** RJ-45 Ethernet x 1,DC12V
- Power-** DC12V or PoE IEEE802.3af Class 0 (optional)
- Max. Power Consumption-** 3.6W(IR OFF) 、 10W(IR ON)
- Weight-** N.W. : 350g
- Dimension-** W:Φ120mm H:70mm
- Operating Environments-** 0 ~ 45 °C

Version updating is not going to inform, please check the on-going updating information