

VIG-DJ797-Z5 1080P

Out Door IP camera




H.265+



CMOS
1/3"



LENS
3.6 mm



4 LEDs



0 LUX



IR
30 M



DC 12V



0~45°C



P.O.E

VIG-DJ797E-Z5
(Optional)



- › 2MP 1/3" CMOS Image Sensor
- › Real-time H.265+, H.264, MJPEG compression (Dual Codec)
- › Maximum resolution 1920x1080 at 30 fps
- › 4 High Power IR LEDs, IR Range 30 M
- › Support ONVIF international standard, best compatibility and integration

| 商品規格

System- Flash: 16MB

RAM: 128MB

Image Sensor- FullHD High Quality 1/3" CMOS Image Sensor

Lens- 3.6 mm

ICR- Built-in Magnetic Infrared Filter Switch

Minimum Illumination- 0 Lux (IR ON)

Number of LED Indicators- High Power IR LEDS x4

Image- H.265+: 1920x1080 at 30 fps

H.265+: 1280x720 at 30 fps

H.265+: 640x480 at 30 fps

H.265+, H.264, JPEG Multi-mode compression (Dual Codec)

Support Simultaneous multiple streams

Image Adjustment- Adjustable Image Size, Quality and Transmission Speed

Time, date, or custom text can be displayed on the image and the display position can be set.

Adjustable brightness, contrast, saturation and sharpness

Support AGC, AWB, AES, BLC, WDR Features

Electronic Shutter- 1/2 ~ 1/100,000 Sec

Network Interface- 10 /100 Mbps Ethernet, RJ-45

Communication Protocol- IPv4, TCP/IP, DHCP, HTTP, RTSP, SNTP, DNS

Browser- Microsoft Internet Explorer 6.0 or above

Safari, Chrome or Firefox

Alarm and Event Management- Motion Detection

Notify via E-mail or upload files to FTP

Users- 8 clients online monitoring simultaneously

Multi-level user access control with password protection

Version updating is not going to inform, please check the on-going updating information

| 商品規格

Maintenance- Supports FOTA

I/O- RJ-45 Ethernet x1, DC 12V Jack x1

Power- DC12V or PoE IEEE802.3af Class 0(optional)

Max. Power Consumption- 3.6W(IR OFF), 7W(IR ON)

Weight- Net weight: 251 g

Dimension (WxDxH)- 98mm x 109mm x 109mm

Operating Environment- 0 ~ 45 °C

Version updating is not going to inform, please check the on-going updating information