

VIG-DS782-D2 1080P

IP Camera



(Optional)



- > 2M Pixel 1/2.8" CMOS Sensor with excellent image quality
- > Real time H.265+/H.264 /MJPEG Multi-Mode compression (Dual Codec)
- > Resolution 1920*1080 @ 30fps/s
- > 12pcs IR LED, IR Distance 15M
- > Support ONVIF international standard, best compatibility and integration

SPECIFICATIONS

System-	Flash : 16MB RAM : 128MB
Sensor-	FullHD High Quality 1/2.8" CMOS Image Sensor
Lens-	Board Lens 3.6 mm F2.0
IR Cut-	Removable IR Cut filter
Lux-	0 Lux(IR ON)
IR LED-	IR LED 12pcs

Compression-	H.265+: 1920x1080 at 30fps H.265+: 1280x720 at 30 fps H.265+: 640x480 at 30fps H.265+ 、 H.264 、 JPEG Multi-mode compression (Dual Codec) Multi-mode compression streaming
---------------------	---

Video Adjustment-	Resolution 、 Quality and bit rate Time 、 Date or custom text and it's position Brightness, Contrast, Saturation and Sharpness AGC 、 AWB 、 AES 、 BLC 、 WDR
--------------------------	--

Network Interface-	10 /100 Mbps RJ-45
Protocol-	IPv4,TCP/IP, DHCP, HTTP, RTSP,SNTP,DNS
Browser-	Microsoft Internet Explorer 6.0 or above Safari, Chrome or Firefox

Alarm & Event notification-	Motion Detection E-mail notification or upload file to FTP
User-	Max. 8 users for live view simultaneously User Authorization
OTA-	OTA for Firmware upgrade

Version updating is not going to inform, please check the on-going updating information

SPECIFICATIONS

I/O Port- RJ-45, DC12V

Power- DC12V or PoE IEEE802.3af Class 0(Optional)

Power Consumption- 3.6W(IR OFF) 、7W(IR ON)

Weight- N.W. : 450g

Dimension- Φ 120 x 60 mm

Operating Environments- 0 ~ 45 °C

Version updating is not going to inform, please check the on-going updating information

Distributed BY

FUHO TECHNOLOGY CO., LTD.

Head Office: No. 30, Lane 726, Jinma Rd, Sec. 3, Chang Hua City, Taiwan 500. TEL:886-4-751-2881

www.vacron.com