

# VIG-UJ739A-Z5 1080P / IP66

## IP Camera



CMOS  
1/3"



36 LEDs



H.265+



35 M



DC 12V



LENS  
3.6mm



P.O.E

(Optional)



- > 2M Pixel 1/3" CMOS Sensor with excellent image quality
- > Real time H.265+ / H.264 / MJPEG Multi-Mode compression (Dual Codec)
- > Resolution 1920\*1080 @ 30fps
- > 36pcs IR LED, IR Distance 35M
- > Support ONVIF international standard, best compatibility and integration

## SPECIFICATIONS

---

<b>System-</b>	Flash : 16MB RAM : 128MB
<b>Sensor-</b>	FullHD High Quality 1/3" CMOS Image Sensor
<b>Lens-</b>	Board Lens 3.6 mm F2.0
<b>IR Cut-</b>	Removable IR Cut filter
<b>Lux-</b>	0 Lux(IR ON)
<b>IR LED-</b>	IR LED 36pcs

---

<b>Compression-</b>	H.265+: 1920x1080 at 30fps H.265+: 1280x720 at 30 fps H.265+: 640x480 at 30fps H.265+ 、 H.264 、 JPEG Multi-mode compression (Dual Codec) Multi-mode compression streaming
---------------------	---

<b>Video Adjustment-</b>	Resolution 、 Quality and bit rate Time 、 Date or custom text and it's position Brightness, Contrast, Saturation and Sharpness AGC 、 AWB 、 AES 、 BLC 、 WDR
--------------------------	--

<b>Network Interface-</b>	10 /100 Mbps RJ-45
<b>Protocol-</b>	IPv4,TCP/IP, DHCP, HTTP, RTSP,SNTP,DNS
<b>Browser-</b>	Microsoft Internet Explorer 6.0 or above Safari, Chrome or Firefox

<b>Alarm &amp; Event notification-</b>	Motion Detection E-mail notification or upload file to FTP
<b>User-</b>	Max. 8 users for live view simultaneously User Authorization
<b>OTA-</b>	OTA for Firmware upgrade
<b>I/O Port-</b>	RJ-45, DC12V
<b>Power-</b>	DC12V or PoE IEEE802.3af Class 0(Optional)

---

Version updating is not going to inform, please check the on-going updating information

## | SPECIFICATIONS

---

<b>Power Consumption-</b>	3.6W(IR OFF) 、 7W(IR ON)
<b>Weight-</b>	310g
<b>Dimension-</b>	200mm x 63mm x 63mm
<b>Operating Environments-</b>	0 ~ 45 °C
<b>IP Rating-</b>	IP66

---

Version updating is not going to inform, please check the on-going updating information

Distributed BY

FUHO TECHNOLOGY CO., LTD.