

# VIG-US729V-D6 5MP / IP66

## IP Camera



(Optional)



- › SONY 5M Pixels 1/2.8" CMOS Sensor with excellent image quality
- › Real time H.265+/H.264 /MJPEG Multi-Mode compression (Dual Codec)
- › Resolution 2560\*1920 @ 15fps/s
- › 56pcs IR LED, IR Distance 40M
- › Support ONVIF international standard, best compatibility and integration

## SPECIFICATIONS

---

- System-** Flash : 16MB  
RAM : 256MB
  - Sensor-** Full HD High Quality 1/2.8" SONY CMOS Image Sensor
  - Lens-** Vari-focal 2.8~12mm F1.8
  - IR Cut-** Removable IR Cut filter
  - Lux-** 0 Lux(IR ON)
- 

- LED-** 56pcs IR LED
  - Compression-** H.265+: 2560x1920 at 15fps  
H.265+: 2048x1536 at 20 fps  
H.265+: 1920x1080 at 30fps  
H.265+ 、 H.264 、 JPEG Multi-mode  
compression (Dual Codec)  
Multi-mode compression streaming
  - Video Adjustment-** Resolution 、 Quality and bit rate  
Time 、 Date or custom text and it's position  
Brightness, Contrast, Saturation and Sharpness  
AGC 、 AWB 、 AES 、 BLC 、 WDR
  - Network Interface-** 10 /100 Mbps RJ-45
    - Protocol-** IPv4,TCP/IP, DHCP, HTTP, RTSP,SNTP,DNS
    - Browser-** Microsoft Internet Explorer 6.0 or above  
Safari, Chrome or Firefox
  - Alarm & Event notification-** Motion Detection  
E-mail notification or upload file to FTP
  - User-** Max. 8 users for live view simultaneously  
User Authorization
  - OTA-** OTA for Firmware upgrade
  - I/O Port-** RJ-45, DC12V
- 

Version updating is not going to inform, please check the on-going updating information

## SPECIFICATIONS

---

<b>Power-</b>	DC12V
<b>Power Consumption-</b>	3.6W(IR OFF) 、 18W(IR ON)
<b>Weight-</b>	N.W. : 1135g
<b>Dimension-</b>	260mm x 118mm x 110mm
<b>Operating Environments-</b>	0 ~ 45 °C
<b>IP Rating-</b>	IP66

---

Version updating is not going to inform, please check the on-going updating information

Distributed BY

FUHO TECHNOLOGY CO., LTD.

Head Office: No. 30, Lane 726, Jinma Rd, Sec. 3, Chang Hua City, Taiwan 500. TEL:886-4-751-2881

[www.vacron.com](http://www.vacron.com)