

VIG-US731T-D2 1080P / IP66

IP camera



- › 2M Pixels 1/2.8" CMOS Sensor with excellent image quality
- › Strengthen night monitoring. Excellent low-light sensitivity
- › Built in electronic auto AF Lens motor, user friendly for remote config
- › Real time H.265+/H.264 /MJPEG Multi-Mode compression (Dual Codec)
- › Resolution 1920*1080 @ 30fps/s
- › HI-POWER LED 8PCS, IR Distance 30M
- › Support ONVIF international standard, best compatibility and integration

SPECIFICATIONS

Ssystem- Flash : 16MB
RAM : 256MB

Image Sensor- Full HD High Quality 1/2.8" CMOS Image Sensor

Lens- Auto Varifocal 2.8-12mm f1.4

IR-cut- Removable IR Cut filter

Low Lux- 0 Lux(IR ON)

IR LED- HI-POWER LED 8PCS

Compression- H.265+: 1920x1080 at 30fps
H.265+: 1280x720 at 30 fps
H.265+: 640x480 at 30fps
H.265+ 、 H.264 、 JPEG Multi-mode compression (Dual Codec)
Multi-mode compression streaming

Image Settings- Resolution 、 Quality and bit rate
Time 、 Date or custom text and it's position
Brightness, Contrast, Saturation and Sharpness
AGC 、 AWB 、 AES 、 BLC 、 WDR

Network Interface- 10 /100 Mbps RJ-45

Protocol- IPv4,TCP/IP, DHCP, HTTP, RTSP,SNTP,DNS

Browser- Microsoft Internet Explorer 6.0 or above
Safari, Chrome or Firefox

Alarm & Event notification- Motion Detection
E-mail notification or upload file to FTP

User- Max. 8 users for live view simultaneously
User Authorization

OTA- OTA for Firmware upgrade

I/O Port- RJ-45, DC12V

Power- DC12V or PoE IEEE802.3af Class 0 (optional)

Version updating is not going to inform, please check the on-going updating information

SPECIFICATIONS

Power Consumption- 3.6W(IR OFF) 、18W(IR ON)

Weight- N.W. : 965g

Dimension- 315 × 88 × 87 mm

Operating Environments- 0 ~ 45 °C

IP Rating- IP66

Version updating is not going to inform, please check the on-going updating information

Distributed BY

FUHO TECHNOLOGY CO., LTD.

Head Office: No. 30, Lane 726, Jinma Rd, Sec. 3, Chang Hua City, Taiwan 500. TEL:886-4-751-2881

www.vacron.com