

VIG-US760-D6 5MP / IP66

IP Camera



- > Sony 5MP 1/2.8" COMS Image Sensor
- > Real-time H.264,H.265+,Mjpeg Compression(dual codec)
- > Highest Resolution 2560x1920 @15 fps
- > HI-POWER LED 8PCS , 30M IR ranges
- > Support ONVIF international standard, best compatibility and integration

SPECIFICATIONS

system- Flash : 16MB

RAM : 256MB

Image Sensor- FullHD High Quality 1/2.8" SONY CMOS Image Sensor

Lens- Board Lens 3.6 mm

IR-cut- Removable IR-cut filter for day & night function

Low Lux- 0.01Lux

Video- H.265+:2560x1920 at 15fps

H.265+: 2048x1536 at 20fps

H.265+: 1920x1080 at 30 fps

Compression: H.264, H.265+, MJPEG

Streaming: Dual Codec Selectable

Support Simultaneous multiple streams

Image Settings- Adjustable image size, quality, and bit rate

Time/Date stamp and text caption overlay

Configurable brightness, contrast, saturation,

sharpness, white balance and exposure

Have: AGC 、 AWB 、 AES 、 BLC 、 WDR Features

Networking Interface- 10 /100 Mbps ,RJ-45

Protocol- IPv4, TCP/IP, DHCP, HTTP, RTSP, SNTP, DNS

browser- Microsoft Internet Explorer 6.0 or above

Safari, Chrome or Firefox

Alarm and Event Management- Motion Detection

FTP Event notification using SMTP or FTP

Users- 8 clients on-line monitoring at the same time

Multi-level user access control with password protection

Version updating is not going to inform, please check the on-going updating information

SPECIFICATIONS

Maintenance-	Supports online firmware upgrade
I/O-	RJ-45 Ethernet x 1,DC12V
Power-	VIG-US760-D6: DC12V VIG-US760E-D6: DC12V or PoE IEEE802.3af Class 0 (optional)
Max. Power Consumption-	3.6W(IR OFF) 、 12W(IR ON)
Weight-	N.W. : 650g
Dimension-	255mm x 75.3mm x 75mm
Operating Environments-	0 ~ 45 °C
IP Rating-	IP66

Version updating is not going to inform, please check the on-going updating information