VIN-DJ771HE-F7 5MP

IP Camera

H.265	4 LEDS	25 M	CMOS 1/2.5"	LENS 3.6mm	DC 12V	0 LUX	P.O.E

> 5MP Pixel 1/2.5" CMOS Sensor with excellent image quality.

> Low-Noise Surrounding Sound Receiver Function.

> AI intelligence humanoid detection function replaces traditional displacement detection system.

> Real-time H.265/H.264 /MJPEG.

> Multi-Mode compression. (Dual Codec) Resolution 2560*1920 @ 30fps/ss.

> 4 HI-P LED, IR Distance to 25M.

> Support ONVIF international standard, the best compatibility and integration.

SPECIFICATIONS

system-	Flash：128MB
	RAM：128MB
Sensor-	FullHD High Quality 1/2.5" CMOS Image Sensor
Lens-	Board Lens 3.6 mm
IR Cut-	Removable IR Cut filter
Lux-	0 Lux (IR ON)
IR LED-	HI-P 4 IR LED

Compression-	H.265 : 2560x1920 at 30fps
	H.265 : 1920x1080 at 30 fps
	H.265、H.264、JPEG Multi-mode
	compression (Dual Codec)
	Multi-mode compression streaming
Video Adjustment-	Resolution、Quality and bit rate
	Time、Date or custom text and it's position
	Brightness, Contrast, Saturation and Sharpness
	AGC、AWB、AES、BLC、WDR
Network Interface-	10 /100 Mbps RJ-45
Protocol-	IPv4, TCP/IP, DHCP, HTTP, RTSP, SNTP, DNS
Browser-	Microsoft Internet Explorer 6.0 or above
	Safari, Chrome or Firefox
Alarm & Event notification-	Motion Detection
	E-mail notification or upload file to FTP
User-	Max. 8 users for live view simultaneously
	User Authorization
OTA-	OTA for Firmware upgrade

Version updating is not going to inform, please check the on-going updating information

VACRON ADVANCES IN SECURITY SOLUTIONS

FUHO TECHNOLOGY CO., LTD.
Head Office: No. 30, Lane 726, Jinma Rd, Sec. 3, Chang Hua City,Taiwan 500. TEL:886-4-751-2881

www.vacron.com

SPECIFICATIONS

I/O Port-	RJ-45, DC12V
Power-	DC12V or PoE IEEE802.3af Class 0
Power Consumption-	3.6W (IR OFF)、7W (IR ON)
IP Rating-	IP66
Weight-	N.W.：285g
Dimension-	Φ 110 x 95 mm
Operating Environments-	0 ~ 45 °C

Version updating is not going to inform, please check the on-going updating information