

VIN-DS755V-E8 8MP

IP camera



H.265



CMOS
1/2.8"



LENS
3.6-11mm



24 LEDs



0 LUX



IR
15 M



DC 12V



-0~45°C



P.O.E

VIN-DS755VE-E8
(Optional)



- > SONY 8MP Pixels 1/2.8" CMOS Sensor with excellent image quality
- > Real time H.265/H.264 Multi-Mode compression (Dual Codec)
- > Resolution 3840x2160 @ 30fps
- > 24pcs IR LED, IR Distance 15M
- > Support ONVIF international standard, best compatibility and integration

SPECIFICATIONS

System-	Flash: 256MB RAM: 512MB
Image Sensor-	Full HD High Quality 1/2.8" SONY CMOS Image Sensor
Lens-	Varifocal 3.6~11mm
ICR-	Removable IR Cut filter
Low Lux-	0 Lux (IR ON)
Number of LED-	24pcs IR LED

Image-	H.265/H.264: 3840x2160 at 30 fps H.265/H.264: 3072x2048 at 30 fps H.265/H.264: 2592x1944 at 30 fps H.265/H.264: 2560x1440 at 30 fps H.265/H.264: 2048x1536 at 30 fps H.265、H.264 Multi-mode compression (Dual Codec) Multi-mode compression streaming
Image Adjustment-	Resolution、Quality and bit rate Time、Date or custom text and it's position Brightness, Contrast, Saturation and Sharpness AGC、AWB、AES、BLC、WDR
Electronic Shutter-	1/2 ~ 1/100,000 Sec
Network Interface-	10 /100 Mbps RJ-45
Communication Protocol-	IPv4,TCP/IP, DHCP, HTTP, RTSP,SNTP,DNS
Browser-	Microsoft Internet Explorer 6.0 or above Safari, Chrome or Firefox
Alarm and Event Management-	Motion Detection E-mail notification or upload file to FTP

Version updating is not going to inform, please check the on-going updating information

| SPECIFICATIONS

Users-	Max. 8 users for live view simultaneously User Authorization
Maintenance-	OTA for Firmware upgrade
I/O-	RJ-45, DC12V
Power-	DC12V or PoE IEEE802.3af Class 0 (optional)
Max. Power Consumption-	3.6W(IR OFF), 10W(IR ON)
Weight-	Net Weight: 690g
Dimension-	W:Φ135mm, H:110mm
Operating Temperature-	0 ~ 45 °C

Version updating is not going to inform, please check the on-going updating information