
VIN-UJ709HE-FB 1080P

AI Humanoid Detection Webcam



(Optional)







- 2MP 1/2.8" CMOS Image Sensor with excellent image quality
- Low-Noise Omnidirectional Audio Pickup, and optional speaker for to two-way communication.
- AI intelligent humanoid detection function replaces the traditional displacement detection system.
- Real-time H.265/H.264 compression (Dual Codec)
- Maximum resolution 1920x1080 at 30 fps
- 4 High Power IR LEDS, IR Range 30 M
- Support ONVIF international standard, best compatibility and integration

VIN-UJ709HE-FB Detailed Information

SPECIFICATIONS

System-	Flash：128MB
	RAM：128MB
Image Sensor-	FullHD High Quality 1/2.8" CMOS Image Sensor
Lens-	3.6mm
IR-cut-	Built-in Magnetic Infrared Filter Switch
Low Lux-	0 Lux(IR ON)
IR LEDs-	High Power IR LEDS X 4

Image Quality-	H.265/H.264: 1920x1080 at 30 fps
	H.265/H.264: 640x480 at 30 fps
	H.265 & H.264 Multimode Engine Compression Technology (Daul Codec)
	Support simultaneous multiple streams
Image Adjustment-	Adjustable image size, quality, and bit rate
	Time, date, or custom text can be displayed on the image, and the display position can be set.
	Adjustable brightness, contrast, saturation, and sharpness
	Support AGC、AWB、AES、BLC、WDR Features
Audio output-	2W Speaker (Optional)
Electronic Shutter-	1/2 ~ 1/100,000 Sec
Network Interface-	10/100 Mbps Ethernet, RJ-45
Communication Protocol-	IPv4、TCP/IP、DHCP、HTTP、RTSP、SNTP、DNS
Browser-	Microsoft Internet Explorer 6.0 or above
	Safari, Chrome or Firefox
Alarm and Event Management-	Human Detection Alarm
	(Alarm Zone setting and Intrusion Alarm setting)
	Notify via email or upload files to FTP

Version updating is not going to inform, please check the on-going updating information

SPECIFICATIONS

Users-	8 clients online monitoring simultaneously
	Multi-level user access control with password protection
Maintenance-	Supports FOTA
I/O-	RJ-45 network port, power input port DC12V
Power-	DC12V or PoE IEEE802.3af Class 0
Max. Power Consumption-	3.6W(IR OFF) 、18W(IR ON)
Weight-	Net weight: 502 g
Dimensions-	71mm x 70mm x 161mm
Operating Temperature-	-20 ~ 45 °C

Version updating is not going to inform, please check the on-going updating information