

VIN-UJ731HV-F7 5MP IP67

IP Camera with Basic Human Detection



- › 5M Pixels 1/2.5" CMOS Sensor with excellent image quality.
- › AI intelligent humanoid detection function replaces traditional displacement detection system.
- › Real time H.265/H.264 Multi-Mode compression. (Dual Codec)
- › Resolution 2592x1944 @ 30fps/s
- › HI-P 8 LED, IR Distance 30M
- › Support ONVIF international standard, best compatibility and integration.

SPECIFICATIONS

System-	Flash : 256MB RAM : 512MB
Sensor-	Full HD High Quality 1/2.5" CMOS Image Sensor
Lens-	Vari-focal 2.8~12mm
IR Cut-	Removable IR Cut filter
Lux-	0 Lux(IR ON)
IR LED-	HI-P 8 LED

Compression-	H.265/H.264: 2592x1944 at 30 fps H.265/H2.64: 1920x1080 at 30 fps H.265 、H.264 Multi-mode compression (Dual Codec) Multi-mode compression streaming
---------------------	--

Video Adjustment-	Resolution 、Quality and bit rate Time 、Date or custom text and it's position Brightness, Contrast, Saturation and Sharpness AGC 、AWB 、AES 、BLC 、WDR
--------------------------	--

Electronic Shutter-	1/2 ~ 1/100,000 Sec
----------------------------	---------------------

Network Interface-	10 /100 Mbps RJ-45
---------------------------	--------------------

Protocol-	IPv4,TCP/IP, DHCP, HTTP, RTSP,SNTP,DNS
------------------	--

Browser-	Microsoft Internet Explorer 6.0 or above Safari, Chrome or Firefox
-----------------	---

Alarm & Event notification-	Motion Detection E-mail notification or upload file to FTP
--	---

User-	Max. 8 users for live view simultaneously User Authorization
--------------	---

OTA-	OTA for Firmware upgrade
-------------	--------------------------

I/O Port-	RJ-45, DC12V,Audio in
------------------	-----------------------

Version updating is not going to inform, please check the on-going updating information

| SPECIFICATIONS

Power-	DC12V or PoE IEEE802.3af Class 0 (optional)
Power Consumption-	3.6W(IR OFF) 、 12W(IR ON)
Weight-	N.W. : 965g
Dimension-	315 x 88 x 87 mm
Operating Environments-	0 ~ 45 °C
IP Rating-	IP67

Version updating is not going to inform, please check the on-going updating information