

VIG-US760-D4 1080P IP66

Starlight full color













(Optional



- > Sony 2MP 1/2.8" COMS Image Sensor
- > Real-time H.264, H.265+, Mjpeg Compression (dual codec)
- > Highest Resolution 1920x1080 @30 fps
- > Starlight full color day and night. With starlight F1.0 HD lens
- > Support ONVIF international standard, best compatibility and integration

VIG-US760-D4 Detailed Information

SPECIFICATIONS

system- Flash: 16MB

RAM: 256MB

Image Sensor- SONY FullHD High Quality 1/2.8" CMOS Image Sensor

Lens- Board Lens 4.0 mm F1.0

IR-cut- Removable IR-cut filter for day & night function

Low Lux- 0.01Lux Starlight full color

Video- H.265+: 1920x1080 at 30fps

H.265+: 1280x720 at 30 fps

H.265+: 640x480 at 30fps

Compression: H.264, H.265+, MJPEG Streaming:

Dual Codec Selectable

Support Simultaneous multiple streams

Image Settings- Adjustable image size, quality, and bit rate

Time/Date stamp and text caption overlay

Configurable brightness, contrast, saturation, sharpness,

white balance and exposure

Have: AGC \ AWB \ AES \ BLC \ WDR Features

Networking Interface- 10 /100 Mbps ,RJ-45

Protocol- IPv4,TCP/IP, DHCP, HTTP, RTSP,SNTP,DNS

browser- Microsoft Internet Explorer 6.0, Safari, Chrome, Firefox

Alarm and Event Management- Motion Detection

Event notification using SMTP or FTP

Users- 8 clients on-line monitoring at the same time

Multi-level user access control with password protection

Maintenance- Supports online firmware upgrade

I/O- DC12V RJ-45 Ethernet x 1,DC12V

Power- DC12V or PoE IEEE802.3af Class 0 (optional)

Version updating is not going to inform, please check the on-going updating information



Distributed BY

VIG-US760-D4 Detailed Information

SPECIFICATIONS

Max. Power Consumption- 3.6W(IR OFF) > 7W(IR ON)

Weight- Net weight: 1050g

Dimension- 195mm x 100mm x 85mm

Operating Environments- 0 ~ 45 °C

IP Rating- IP66

Version updating is not going to inform, please check the on-going updating information

