

VIG-US760T-D6 5MP / IP66

Electronic Auto AF motor lens IP camera



(Optional)



- > Sony 5MP 1/2.8" COMS Image Sensor
- > Built in electronic auto AF Lens motor, user friendly for remote config
- > Real-time H.264,H.265+,Mjpeg Compression(dual codec)
- > Highest Resolution 2560x1920 @15 fps
- > HI-POWER LED 8PCS , 30M IR ranges
- > Support ONVIF international standard, best compatibility and integration

SPECIFICATIONS

system- Flash : 16MB

RAM : 256MB

Image Sensor- FullHD High Quality 1/2.8" SONY CMOS Image Sensor

Lens- Auto Varifocal 2.8-12mm f1.4

IR-cut- Removable IR-cut filter for day & night function

Low Lux- 0 .01Lux

Video- H.265+:2560x1920 at 15fps

H.265+: 2048x1536 at 20fps

H.265+: 1920x1080 at 30 fps

Compression: H.264, H.265+, MJPEG Streaming:

Dual Codec Selectable

Support Simultaneous multiple streams

Image Settings- Adjustable image size, quality, and bit rate

Time/Date stamp and text caption overlay

Configurable brightness, contrast, saturation, sharpness, white balance and exposure

Have: AGC 、AWB 、AES 、BLC 、WDR Features

Networking Interface- 10 /100 Mbps ,RJ-45

Protocol- IPv4, TCP/IP, DHCP, HTTP, RTSP, SNTP, DNS

browser- Microsoft Internet Explorer 6.0 Safari, Chrome, Firefox

Alarm and Event Management- Motion Detection

Event notification using SMTP or FTP

Users- 8 clients on-line monitoring at the same time

Multi-level user access control with password protection

Maintenance- Supports online firmware upgrade

I/O- DC12V RJ-45 Ethernet x 1, DC12V

Power- DC12V or PoE IEEE802.3af Class 0 (optional)

Version updating is not going to inform, please check the on-going updating information

| SPECIFICATIONS

Max. Power Consumption- 3.6W(IR OFF) 、 7W(IR ON)

Weight- Net weight:650g

Dimension- 255mm x 75.3mm x 75mm

Operating Environments- 0 ~ 45 °C

IP Rating- IP66

Version updating is not going to inform, please check the on-going updating information

Distributed BY

FUHO TECHNOLOGY CO., LTD.